

THAWZALL™
Manufactured by T.H.E. Machine Company

MODEL 2M SPECIFICATIONS AND PERFORMANCE

SPECIFICATIONS: MODEL 2M

Height	78 Inches
Width	74 Inches
Length	144 Inches
Weight (Including Fuel)	3,006 Lbs.
Fuel Capacity	100 U.S. Gal.
Heat Transfer Fluid Capacity	56 U.S. Gal.
Hose	1,200 Feet Supplied
Circulation Zones	2
Circulation Pump	1 High Output Pump
Fill Pump	1
Tires	225x75R16
Axle	3,500 Lb. Torflex
Brakes	Electric

PERFORMANCE: MODEL 2M

Heat Input	140,000 BTU
Max Fuel Consumption	1.0 U.S. Gal./Hour
Fuel Requirements	#1 Fuel Oil or #1 Diesel Fuel
Electrical Requirements	1 - 120 VAC 20 AMP
Normal Operating Temperature	Supply 180 ° F
Maximum Thawing Capacity	2,400 Sq. Ft.
Concrete Curing Capacity	6,000 Sq. Ft.
Generator (Optional)	Call for Options

THAWZALL™
Manufactured by T.H.E. Machine Company

MODEL 6A SPECIFICATIONS AND PERFORMANCE

SPECIFICATIONS: MODEL 6A

Height	91 Inches
Width	84 Inches
Length	170 Inches
Weight (Including Fuel)	5,605 Lbs.
Fuel Capacity	160 U.S. Gal.
Heat Transfer Fluid Capacity	122 U.S. Gal.
Hose	3,000 Feet Supplied
Circulation Zones	5
Remote Manifold Outlet	1
Circulation Pump	2 High Output Pumps
Fill Pump	1
Tires	225x75R16
Axle	6,000 Lb. Torflex
Brakes	Electric

PERFORMANCE: MODEL 6A

Heat Input	280,000 BTU
Max Fuel Consumption	1.75 U.S. Gal./Hour
Fuel Requirements	#1 Fuel Oil or #1 Diesel Fuel
Electrical Requirements	1 - 120 VAC 20 AMP
Normal Operating Temperature	Supply 180° F
Maximum Thawing Capacity	6,000 Sq. Ft.
Concrete Curing Capacity	18,000 Sq. Ft.
Generator (Optional)	Call for options

THAWZALL™
Manufactured by T.H.E. Machine Company

MODEL 12HU SPECIFICATIONS AND PERFORMANCE

SPECIFICATIONS: MODEL 12HU

Height	91 Inches
Width	84 Inches
Length	170 Inches
Weight (Including Fuel)	4,350 Lbs.
Fuel Capacity	300 U.S. Gal.
Heat Transfer Fluid Capacity	138 U.S. Gal.
Circulation Zones	5
Remote Manifold Outlet	1
Circulation Pump	1 High Output Pump
Fill Pump	1
Tires	225x75R16
Axle	6,000 Lb. Torflex
Brakes	Electric

PERFORMANCE: MODEL 12HU

Heat Input	560,000 BTU
Fuel Consumption	3.5 U.S. Gal.
Max Fuel Requirements	#1 Fuel Oil or #1 Diesel Fuel
Electrical Requirements	1 -120 VAC 20 AMP
Normal Operating Temperature	Supply 180° F
Maximum Thawing Capacity	12,000 Sq. Ft.
Concrete Curing Capacity	36,000 Sq. Ft.
Generator (Optional)	7kW Isuzu Liquid Cooled

THAWZALL™
Manufactured by T.H.E. Machine Company

MODEL 12F SPECIFICATIONS AND PERFORMANCE

SPECIFICATIONS: MODEL 12F

Height	91 Inches
Width	100 Inches
Length	233 Inches
Weight (Including Fuel)	10,378 Lbs.
Fuel Capacity	300 U.S. Gal.
Heat Transfer Fluid Capacity	244 U.S. Gal.
Hose	6,000 Feet Supplied
Circulation Zones	10
Remote Manifold Outlet	2
Circulation Pump	2 High Output Pumps
Fill Pump	1 Standard
Tires	225x75R16
Axle	Dual 6,000 Lb. Torflex
Brakes	Electric

PERFORMANCE: MODEL 12F

Heat Input	560,000 BTU
Max Fuel Consumption	3.5 U.S. Gal./Hour
Fuel Requirements	#1 Fuel Oil or #1 Diesel Fuel
Electrical Requirements	2 - 120 VAC 20 AMP
Normal Operating Temperature	Supply 180° F
Maximum Thawing Capacity	12,000 Sq. Ft.
Concrete Curing Capacity	36,000 Sq. Ft.
Generator (Optional)	10 kW Isuzu Liquid